



Fiber blowing machine for FTTH fibers (EPFU) and micro cables up to 4.5 mm and ducts up to 12.7 mm.

ADJUSTABLE CLAMPING FORCE

Secures grip around cable/fiber during installation.

TOOL FREE INSTALLATION

Easy to open and close by hand with quick load of fiber and duct. Adjustable speed and torque. Battery-powered.

LED DISPLAY

Shows speed, distance, fiber protection and battery information.

UNIQUE FIBER PROTECTION TECHNOLOGY

If the maximum recommended load on the fiber exceeds the preset torque, the machine stops the blowing process immediately without damaging the fiber.

TESTED IN ACCORDANCE TO IEC STANDARDS

INCLUDED

- 2 x 24V 2.0 Ah Lithium-ion battery with quick charger
- Filter and water separator
- 1 adapter plate set 4.8 mm
- Steel drive wheel for fibers + 3 mm
- Drive wheel for fibers 0.8 - 3 mm
- Duct adapters for 3, 5, 7, 8, 8.5, 10, 12, 12.7 mm

AVAILABLE ACCESSORIES

- Tripod with quick adapter
Item No.: J103-161127005
- Shoulder strap
Item No.: J103-160601074
- Reel holder arm for pre-connected fiber
Item No.: J103-171020001
- Steel drive wheel for up to 3 mm fiber
Item No.: J103-170515001
- 24V 4.0 Ah Lithium-ion battery
Item No.: J103-160601043

A wide selection of adapter plates for any fiber/duct sizes on request



Specifications

Specifications	
Part Number	J101-1909110012
Cable diameter	0.8-4.5 mm
Duct diameter	3-12.7 mm
Blowing distance	Up to 3940 ft. (1200 m)
Blowing speed	Up to 410 ft./min (125 m/min)
Recommended pressure and airflow	Max. 10 bar (150 psi) Max. 200 L/min (7.1 cfm)
Weight	7.7 lbs. (3.5 kg)
Length	8.3 in. (212 mm)
Width	4.1 in. (104 mm)
Height	5.5 in. (139 mm)