



Blank Duct Plugs

Sealing Devices for Ducted Cable Networks

- All plastic construction
- Corrosion proof
- Water-tight
- Easy installation and removal
- Reusable

Blank duct plugs effectively seal conduits to reduce the cost of cable placement and maintenance in new underground construction projects and routine work. These plugs are economical because they are removable and reusable.

Duct Bank Durability

Manufactured from high-impact plastic components, combined with durable elastic gaskets, Blank plugs are corrosion proof and effective as long-term or temporary seals.

Economy and Safety

Both water-tight and gas-tight, Blank duct plugs prevent the flow of water and the costly sedimentation of duct banks and conduit systems while confining problems of dangerous vapors to their source.

Convenience

Each Blank plug is equipped with a rope tie device to allow the securing of pull rope to the plug's back compression plate. Installers can attach the rope to the back compression plate of the plug and store excess slack rope behind the plug within the conduit system for future use.

Part Number	Product Descriptor*	Size	Duct ID Range	
			inch	mm
542288	JM-BLA-07D100U	0.700	0.71 - 0.83	18.0 - 21.1
298182	JM-BLA-10D104U	1.000	0.96 - 1.16	24.4 - 29.5
187308	JM-BLA-12D148U	1.250	1.14 - 1.48	29.0 - 37.6
F64411	JM-BLA-12D163U	1.375	1.30 - 1.63	33.0 - 41.4
036620	JM-BLA-15D183U	1.500	1.49 - 1.83	37.8 - 46.5
923104	JM-BLA-20D236U	2.000	1.83 - 2.36	46.5 - 59.9
121592	JM-BLA-25D296U	2.500	2.34 - 2.96	59.4 - 75.2
162754	JM-BLA-30D346U	3.000	2.99 - 3.46	75.9 - 87.9
061704	JM-BLA-35D400T	3.500	3.45 - 3.80	86.9 - 96.5
828822	JM-BLA-35D400U	3.500	3.45 - 3.80	86.9 - 96.5
758432	JM-BLA-35D400N	3.500	3.45 - 3.80	86.9 - 96.5
RH0166	JM-BLA-38D401-C	3.800	3.80 - 3.94	96.5 - 100.1
MP0236	JM-BLA-40D400T	4.000	3.94 - 4.17	100.1 - 105.9
293842	JM-BLA-40D402N	4.000	3.94 - 4.17	100.1 - 105.9
377850	JM-BLA-40D402U	4.000	3.94 - 4.17	100.1 - 105.9
D54832	JM-BLA-40D402U-C	4.000	3.94 - 4.17	100.1 - 105.9
F90744	JM-BLA-50D500U	5.000	4.58 - 5.02	116.3 - 127.5
934754	JM-BLA-50D535U	5.000	5.00 - 5.35	127.0 - 135.9
F76622	JM-BLA-55D590U-CR	5.500	5.51 - 5.91	140.0 - 150.1
566534	JM-BLA-60D637U	6.000	5.82 - 6.37	147.8 - 161.8
F81950	JM-BLA-70D750U-CR	7.000	7.09 - 7.55	180.1 - 191.8
885144	JM-BLA-80D816U	8.000	7.83 - 8.27	198.9 - 210.1

* T - Temporary Plug, CR- CR Rubber Gasket, C - Custom Gasket, N - Nut Version

Tyco Electronics Corporation
 8000 Purfoy Road
 Fuquay Varina, NC 27526-9349
 Tel: 919-557-8900
 Fax: 919-557-8498
www.tycoelectronics.com
www.telecomosp.com

TE (logo) and Tyco Electronics are trademarks.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, Tyco Electronics makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. Tyco Electronics' obligations shall only be as set forth in Tyco Electronics' Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of Tyco Electronics products should make their own evaluation to determine the suitability of each such product for the specific application.