

HomeConnect® Two-way Splitter, 5–1218 MHz



Product Classification

<b>Brand</b>	HomeConnect®
<b>Product Type</b>	Coaxial splitter

Environmental Specifications

<b>Grounding and Bonding Standard</b>	UL 467 Ground Clamp Communication
<b>Operating Temperature</b>	-40 °C to +60 °C (-40 °F to +140 °F)
<b>Safety Standard</b>	SCTE

Electrical Specifications Isolation

<b>Isolation at Frequency Band, output to output, minimum</b>	25 dB @ 1002–1218 MHz   28 dB @ 205–1002 MHz   30 dB @ 5–10 MHz   35 dB @ 10–205 MHz
---	--

Electrical Specifications

<b>Power Passing</b>	No
<b>Impedance</b>	75 ohm
<b>Operating Frequency Band</b>	5 – 1218 MHz
<b>Return Loss at Frequency Band, input, minimum</b>	18 dB @ 1002–1218 MHz   20 dB @ 5–1002 MHz
<b>Return Loss at Frequency Band, output, minimum</b>	18 dB @ 1002–1218 MHz   20 dB @ 5–1002 MHz
<b>Insertion Loss at Frequency Band, typical</b>	3.6 dB @ 5–400 MHz   4.0 dB @ 1002–1218 MHz   4.0 dB @ 400–1002 MHz
<b>Frequency Response</b>	±0.3 dB
<b>Spurious Signals/2nd Order Harmonics, before surge</b>	<-100 dBc
<b>Shielding Effectiveness, minimum</b>	120 dB
<b>Surge Capability Test Method</b>	ANSI/SCTE 81   Category A3 (6 kV, 200 A, Ring wave)
<b>Surge Capability Waveform</b>	100 kHz ring wave waveform

General Specifications

<b>Device Type</b>	Splitter
<b>Mounting</b>	Horizontal
<b>Video Ports, quantity</b>	2

**Application**

Indoor | Outdoor

## Packed Dimensions

**Carton Quantity**

400

**Height**

215.90 mm | 8.50 in

**Length**

482.60 mm | 19.00 in

**Width**

368.30 mm | 14.50 in

**Shipping Weight**

20.87 kg | 46.00 lb

## Regulatory Compliance/Certifications

**Agency**

RoHS 2011/65/EU

ISO 9001:2015

CE

**Classification**

Designed, manufactured and/or distributed under this quality management system

