

**MATERIAL & STYLE**

Polyolefin Blend  
Straight Wall

**1730-12**

ANSI/SCTE-77, Tier 15  
28.5 lbs

ANSI/SCTE-77, Tier 22  
31.3 lbs

**1730-18**

ANSI/SCTE-77, Tier 15  
36.2 lbs

ANSI/SCTE-77, Tier 22  
41.3 lbs

**1730-24**

ANSI/SCTE-77, Tier 15  
*Available Soon*

ANSI/SCTE-77, Tier 22  
*Available Soon*

	A	B	C
1730-12	20 1/2	33 1/2	12
1730-18	20 1/2	33 1/2	18
1730-24	Available soon		



**MEDIUM DUTY**  
ANSI/SCTE TIER 15



**HEAVY DUTY**  
ANSI/SCTE TIER 22

For use in non-vehicular traffic situations only. Weights and dimensions may vary slightly. Actual load rating is determined by the box and cover combination.

Cover comes standard with permanent markings for manufacturer, load rating, model size and manufacturing location.  
\*Based upon lid and body combination, this unit can be Tier 15 or Tier 22. T22 rating when paired with T22 polymer concrete lid.

Revision 02/03/19

© 2019 Oldcastle Infrastructure, Inc




**OPTIONS**

Available Covers: • Polymer Concrete, Flush Solid



Fasteners: • Hex Head Coil Thread Bolt  
• Penta Head Coil Thread Bolt



Detail: Bolt Down



Add On Options: • Logos and Special Markings • Rack Mount / Cable Rack • Pulling Eye  
• Marking Plate • Cable Arms • Ground Buss  
• EMS Marker • Unistrut • Dividers

**RAW MATERIAL SPECIFICATION**

BODY : Material Property	Test Method	Typical Value <sup>1</sup>
Density	ASTM D1505	0.960 to 0.980, g/cm <sup>3</sup>
Tensile Strength, at break	ASTM D638	5,500 to 7,700 psi
Flexural Modulus	ASTM D790	400,000 to 500,000 psi
Impact Resistance	ASTM D5420	60.0 in-lb

<sup>1</sup> The values listed for physical property measurements are nominal values only. Certain physical property measurements are subject to variations consistent with the test methods and are within a generally accepted range for such values.